

2 Product Specifications

2-1 Specifications

Item	Description
LCD Panel	TFT-LCD panel, RGB vertical stripe, normally white, 15-Inch viewable, 0.297 (H) x 0.297 (V) pixel pitch
Scanning Frequency	Horizontal : 30 kHz to 61 kHz (Automatic) Vertical : 50 Hz to 75 Hz (Automatic)
Display Colors	16,772,216 colors
Maximum Resolution	Horizontal : 1024 Pixels Vertical : 768 Pixels
Input Video Signal	Analog, 0.714 Vp-p \pm 5% positive at 75 Ω , internally terminated
Input Sync Signal	Type: Seperate H/V sync, Composite H/V, Sync-on-Green, automatic synchronization without external switch of sync type Level: TTL level
Maximum Pixel Clock rate	80 MHz
Active Display Horizontal/Vertical	304.1 mm / 228.1 mm
AC power voltage & Frequency	AC 90 to 264 Volts, 60/ 50 Hz \pm 3 Hz
Power Consumption	25 W (max.)
Dimensions Unit (W x D x H) Carton (W x D x H)	15.9x7.7x16.5 Inches (404 x 196 x 419 mm) 18.7 x 11.1 x 20.1 Inches (475 x 282 x 510 mm)
Weight (Net/Gross)	7.4 kg / 9.4kg
Environmental Considerations	Operating Temperature : 50°F to 104°F (10°C to 40°C) Humidity : 10 % to 80 % Storage Temperature : -13°F to 113°F (-25°C to 45°C) Humidity : 5 % to 95 %
Audio Characteristics (optional)	<ul style="list-style-type: none"> • Audio Characteristics • Built-in Microphone: High-sensitivity condenser microphone (mono) • Audio input: Left/Right Stereo phone jack, 0.7 Vrms • Sound output: 16 W (left) + 16 W (right)/THD 1% at 16ohm • Frequency response: 80 Hz~20 kHz (at -3dB) • Headphone: Max 50mW output (3.5-pi jack) • Speaker: Internal semi Dome (16ohm x 2)
<ul style="list-style-type: none"> • SyncMaster 570BTFT/580BTFT complies with SWEDAC (MPR II) recommendations for reduced electromagnetic fields. • Designs and specifications are subject to change without prior notice. 	

2-2 Pin Assignments

<div> <div>Sync Type</div> <div>Pin No.</div> </div>	15-Pin Signal Cable Connector		
	Separate	Composite	Sync-on-green
1	Red	Red	Red
2	Green	Green	Green + H/V Sync
3	Blue	Blue	Blue
4	GND	GND	GND
5	GND (DDC Return)	GND (DDC Return)	GND (DDC Return)
6	GND-R	GND-R	GND-R
7	GND-G	GND-G	GND-G
8	GND-B	GND-B	GND-B
9	No Connection	No Connection	Not Used
10	GND-Sync/Self Test	GND-Sync/Self Test	GND-Sync/Self Test
11	GND	GND	GND
12	DDC Data	DDC Data	DDC Data
13	H-Sync	H/V-Sync	Not Used
14	V-Sync	Not Used	Not Used
15	DDC Clock	DDC Clock	DDC Clock


<div> <div>Sync Type</div> <div>Pin No.</div> </div>	26-Pin Signal Cable Connector		
	Separate	Composite	Sync-on-green
1	Red	Red	Red
2	Green	Green	Green + H/V Sync
3	Blue	Blue	Blue
4	GND	GND	GND
5	GND (DDC Return)	GND (DDC Return)	GND (DDC Return)
6	GND-R	GND-R	GND-R
7	GND-G	GND-G	GND-G
8	GND-B	GND-B	GND-B
9	No Connection	No Connection	Not Used
10	GND-Sync/Self Test	GND-Sync/Self Test	GND-Sync/Self Test
11	GND	GND	GND
12	DDC Data	DDC Data	DDC Data
13	H-Sync	H/V-Sync	Not Used
14	V-Sync	Not Used	Not Used
15	DDC Clock	DDC Clock	DDC Clock
16 ~26	GND	GND	GND

2-3 Timing Chart

This section of the service manual describes the timing that the computer industry recognizes as standard for computer-generated video signals.

Table 2-1. Timing Chart

Mode Timing	IBM			VESA			
	VGA1/70 Hz 640 x 350	VGA2/70 Hz 720 x 400	VGA3/60 Hz 640 x 480	640/72 Hz 640 x 480	640/75 Hz 640 x 480	800/56 Hz 800 x 600	800/60 Hz 800 x 600
fH (kHz)	31.469	31.469	31.469	37.861	37.500	35.156	37.879
A μ sec	31.778	31.777	31.778	26.413	26.667	28.444	26.400
B μ sec	3.813	3.813	3.813	1.270	2.032	2.000	3.200
C μ sec	1.589	1.589	1.589	3.810	3.810	3.556	2.200
D μ sec	26.058	26.058	26.058	20.825	20.317	22.222	20.000
E μ sec	0.318	0.318	0.318	0.508	0.508	0.667	1.000
fV (Hz)	70.086	70.087	59.940	72.809	75.000	56.250	60.317
O msec	14.268	14.268	16.683	13.735	13.333	17.778	16.579
P msec	0.064	0.064	0.064	0.079	0.080	0.057	0.106
Q msec	1.716	0.858	0.794	0.528	0.427	0.626	0.607
R msec	11.504	13.155	15.761	13.100	12.800	17.067	15.840
S msec	0.985	0.191	0.064	0.026	0.027	0.028	0.026
Clock Frequency (MHz)	25.175	28.322	25.175	31.500	31.500	36.000	40.000
Polarity H.Sync	Positive	Negative	Negative	Negative	Negative	Positive	Positive
V.Sync	Negative	Positive	Negative	Negative	Negative	Negative	Positive
Remark	Separate	Separate	Separate	Separate	Separate	Separate	Separate



A : Line time total

B : Horizontal sync width

O : Frame time total

P : Vertical sync width

C : Back porch

D : Active time

Q : Back porch


R : Active time

E : Front porch

S : Front porch

Table 2-1. Timing Chart Continued

Mode Timing	VESA					MAC.	
	800/72 Hz 800 x 600	800/75 Hz 800 x 600	1024/60 Hz 1024 x 768	1024/70 Hz 1024 x 768	1024/75 Hz 1024 x 768	640/67 Hz 60 x 480	832/75 Hz 832 x 624
fH (kHz)	48.077	46.875	48.363	56.476	60.023	35.000	49.726
A μ sec	20.800	21.333	20.677	17.707	16.660	28.571	20.110
B μ sec	2.400	1.616	2.092	1.813	1.219	2.116	1.117
C μ sec	1.280	3.232	2.462	1.920	2.235	3.175	3.910
D μ sec	16.000	16.162	15.754	13.653	13.003	21.164	14.524
E μ sec	1.120	0.323	0.369	0.320	0.203	2.116	0.559
fV (Hz)	72.188	75.000	60.004	70.069	75.029	66.667	74.551
O msec	13.853	13.333	16.666	14.272	13.328	15.000	13.414
P msec	0.125	0.064	0.124	0.106	0.050	0.086	0.060
Q msec	0.478	0.448	0.600	0.513	0.466	1.114	0.784
R msec	12.480	12.800	15.880	13.599	12.795	13.714	12.549
S msec	0.770	0.021	0.062	0.053	0.017	0.086	0.020
Clock Frequency (MHz)	50.000	49.500	65.000	75.000	78.750	30.240	57.284
Polarity H.Sync	Positive	Positive	Negative	Negative	Positive	Negative	Negative
V.Sync	Positive	Positive	Negative	Negative	Positive	Negative	Negative
Remark	Separate	Separate	Separate	Separate	Separate	Separate	Separate



A : Line time total

B : Horizontal sync width

O : Frame time total

P : Vertical sync width

C : Back porch

D : Active time

Q : Back porch

R : Active time

E : Front porch

S : Front porch