

■ SCHEMATIC DIAGRAM

1. CAUTION

THE COMPONENTS MARKED WITH  ON THE SCHEMATIC DIAGRAM HAVE SPECIAL CHARACTERISTICS. IMPORTANT FOR SAFETY AND SHOULD BE REPLACED ONLY WITH TYPES IDENTICAL TO THOSE IN ORIGINAL CIRCUIT OR SPECIFIED IN THE PARTS LIST. DO NOT DEGRADE THE SAFETY OF THE RECEIVER THROUGH IMPROPER SERVICING.

WARNING:

BEFORE SERVICING THIS CHASSIS, READ THE "X-RAY RADIATION PRECAUTION", "SAFETY PRECAUTION" AND "PRODUCT SAFETY NOTICE" IN THE SERVICE MANUAL.

CAUTION TO THE SERVICE TECHNICIANS:

BEFORE RETURNING THE RECEIVER TO THE CUSTOMER, APPROPRIATE LEAKAGE CURRENT OR RESISTANCE MEASUREMENTS SHOULD BE CONDUCTED TO DETERMINE THAT EXPOSED PARTS ARE PROPERLY INSULATED FROM THE SUPPLY CIRCUIT.

NOTES:

1. RESISTANCE IS SHOWN IN OHMS. K=1,000 M=1,000,000

2. UNLESS OTHERWISE NOTED IN THE SCHEMATIC, ALL CAPACITOR VALUES LESS THAN 1 ARE EXPRESSED IN PF AND THE VALUES MORE THAN 1 IN μ F.

3. VOLTAGES READ WITH A "V.T.V.M." ARE MEASURED FROM POINT INDICATED TO CHASSIS GROUND USING A COLOR BAR SIGNAL WITH ALL CONTROLS AT NOMINAL LINE VOLTAGE 100-200V AC. VOLTAGE READINGS SHOWN ARE NOMINAL VALUES AND MAY VARY $\pm 25\%$ EXCEPT H.V.

4. THIS CIRCUIT DIAGRAM IS A STANDARD ONE. CIRCUITS PRINTED MAY BE SUBJECT TO CHANGE FOR PRODUCT IMPROVEMENT WITHOUT PRIOR NOTICE.

