

Service Manual



SPECIFICATIONS

Power Source :	220 - 240 V AC, 50Hz	AV3 IN	S-Video IN (4-pin)	Y : 1V p-p 75Ω C : 0.3V p-p 75Ω
Power Consumption :	239W	AV4 IN	Audio (RCA x 2)	500mV rms 10kΩ
Standby Power Consumption :	1W	AV4 OUT	Video (RCA x 1)	1V p-p 75Ω
Aerial Impedance :	75Ω unbalanced, Coaxial Type			
Receiving System :	PAL I, PAL 525/60 M.NTSC, NTSC (AV Only)		High Voltage :	31 kV ±1kV
Receiving Channels :	VHF A - S20 UHF E21 - E69 CATV S21 - S41 (HYPERBAND)		Picture Tube :	W86KYP881X05 106° deflection
Intermediate Frequency :			Audio Output :	2 x 20W (Left/Right)(Music Power) 14W (Centre built-in)(Music Power) 2 x 15W (Surround)(Music Power) 20W (External)(Music Power) 8Ω Impedance
Video	39.5MHz		Headphones	8Ω Impedance
Sound	33.5MHz			
	32.95MHz			
Colour	35.07MHz			
Video / AudioTerminals :			Accessories supplied :	Remote Control 2 x R6 (UM3) Batteries TS-500DP TV Stand/Speakers
DOLBY SURROUND OUT	Audio (RCA x 5) 500 mV rms 1kΩ		Dimensions :	Height : 618.5mm Width : 894mm Depth : 578.5mm
AV1 IN	Video (21 pin) 1V p-p 75Ω Audio (21 pin) 500mV rms 10kΩ RGB (21 pin)		Net Weight :	73.4kg
AV1 OUT	Video (21 pin) 1V p-p 75Ω Audio (21 pin) 500mV rms 1kΩ			
AV2 IN	Video (21 pin) 1V p-p 75Ω Audio (21 pin) 500mV rms 10 kΩ S-Video IN (21 pin) Y : 1V p-p 75Ω C : 0.3V p-p 75Ω			
AV2 OUT	Video (21 pin) 1V p-p 75Ω Audio (21 pin) 500mV rms 1kΩ Selectable output (21 pin)			


Colour Television

TX-W36D3DP/L EURO-3HWS Chassis


Specifications are subject to change without notice.
Weight and dimensions shown are approximate.


NOTE : This service manual should be used in conjunction with the EURO 3 and Dolby technical guides.


B BOARD 
TNPA0317




C BOARD △
TNP8EC002










G BOARD ▲
TNPA0297



JK3101


AV1


JK3102


AV2


JK3104


AV4












N BOARD ▲
TNPA0763



COLD

